

Model	Fitting Type (3/4" and above have 1/2" NPT up)	Fitting/Stem Material	Number of Levels	Float Options	Options
SSR (SMALL MULTI POINT SWITCH)	125 = (1/8")	1 = S/S	1 = 1 Switch Level	F = 22 X 40mm; S/S, S.G. 0.82	N4 = NEMA 4X
	25 = (1/4")	2 = Brass	2 = 2 Switch Levels	G = 28 X 28mm; S/S, S.G.=0.66	SPDT = Single Pole, Double Throw
	38 = (3/8")		3 = 3 Switch Levels	H = 38 X 26mm; S/S, S.G.=0.56	ADJ = Adjustable
	50 = (1/2")		4 = 4 Switch Levels	J = 25 X 25mm; PP, S.G.=0.7	HT=high temp 125°C max
	75 = (3/4")			K = 26 X 25mm; BUNA, S.G.=0.7	
	100 = (1")			L = 25 X 15mm; BUNA, S.G.=0.5	
	140 = (1 1/4")			M = 18 X 25mm; BUNA, S.G.=0.7	
	150 = (1 1/2")				
	200 = (2")				
	SAE5 = SAE5 FLANGE	S/S ONLY			
	SANF = Sanitary flange	S/S ONLY			
	T = TUBE END				

EXAMPLE:

SSR150-1-4-J-N4

1-1/2"npt, stainless fitting, 4 levels, 25 X 25mm PP floats, NEMA 4X connection head with terminal strip. (Levels and switch state to be selected by customer.)

Level measurements are to be measured from the bottom of the fitting to the switch point, starting with L1 (being closest to the connection)

Switch State needs to be identified for each level. N/O=Normally Open , N/C=Normally Closed, SPDT=Single Pole Double Throw

Length of stem will be 1" longer then the last switch point.

Example: L1 = 2"N/O

L2=6"N/O

L3=9"N/C

L4=12"N/C

LOA=14"